

ISOLIERGRUND-PLUS

INTENDED PURPOSE:	ISOLIERGRUND-PLUS is a white pigmented priming paint for all new and restored plaster bases. It is suitable for both internal and external application. It is used for reducing the absorptive capacity of plaster bases in order to avoid the thin final coats to be applied from drying too quickly and to equalize plaster bases with deviating absorptive capacities. It is also suitable for old plaster.
COMPOSITION/ PROPERTIES:	ISOLIERGRUND-PLUS is based on acrylate dispersion, filler material and colour pigments. ISOLIERGRUND-PLUS is open to diffusion and is alkali resistant.
DELIVERY:	White and – upon special order – also coloured in accordance with the SCHAEFER KRUSEMARK Color-System, as well as special colours. In 15 l buckets.
STORAGE:	To be stored in a cool but frost-free area. The period of storage should not exceed 12 months. Open containers should be kept closed and used as soon as possible.
YIELD:	15 l = 75-80 m ² . The exact usage is to be determined by means of patterning at the object.
UNDERGROUND:	The underground must be solid, clean and able to take a load. There must be no traces of separating agents such as grease, wax or silicones. New floating must be well-dried. Old floating must be cleaned thoroughly. In the case of old dispersion undergrounds, cleaning with steam hoses is not recommended. In the case of fungal decay or growth of algae, a special priming paint as well as an after-treatment with anti-mould agents is recommended.
PROCESSING:	<p>Apply ISOLIERGRUND-PLUS thickly and evenly. The product is ready for use and must not be diluted.</p> <p>ISOLIERGRUND-PLUS should be thoroughly stirred before application. The application shall be carried out either with paint rollers or brushes, evenly and without streaks, depending on the underground. Before applying heat-treated final coats, ISOLIERGRUND-PLUS must be well-dried, i.e., a downtime of at least 24 hours must be complied with.</p> <p>When processing, the general safety regulations must be complied with.</p> <p>All tools are to be cleaned with water immediately after use.</p> <p>ISOLIERGRUND-PLUS must not be used as priming paint on restoration render!</p> <p>ISOLIERGRUND-PLUS may not be used with an air or plaster base temperature of less than 5°C.</p> <p>The same applies up to desiccation.</p>
SAFETY NOTICE:	Mortar reacts with a heavily alkaline effect – avoid contact with the eyes and the skin. Details are shown in the safety data sheet.

The above information is based on tests and experience and represents a general guideline. It cannot be transferred to every specific application and does not release the user from the obligation of carrying out his own tests and trials. The generally recognised and technical rules of building technology as well as relevant standards and guidelines apply. Technical information about further products and our technical consultancy service are available on request. We reserve the right to make technical changes in the interests of ongoing development. In addition, our General Terms and Conditions of Business apply. Revision date: February 2015.

SCHAEFER KRUSEMARK GmbH & Co. KG

Louise-Seher-Str. 6

D-65582 Diez/Germany

Tel. +49 (0) 64 32 / 503 - 0

Fax: +49 (0) 64 32 / 503 - 119

E-Mail: info@schaefer-krusemark.de

Internet: www.schaefer-krusemark.de