

## QUARZGRUND

- INTENDED PURPOSE:** For indoor and outdoor applications QUARZGRUND is mainly used as primer coat for load-bearing, smoothing paints, synthetic resin plasters, oil paints etc. before the application of adhesive and reinforcement mortar.  
As a combustion blocker and adhesion enhancement for mineral lime and/or lime cement as well as plaster substrates which contain gypsum before application of thin-layered mineral and organic top plasters.  
Old gypsum plasters, plasterboards or wooden surfaces must be pre-treated with SPERRGRUND with a solvent base to prevent stain formation (tannic acid, lignin acid).
- COMPOSITION:** QUARZGRUND is a slightly white pigmented primer coat containing quartz sand for plaster. QUARZGRUND is also available in hues according to the SCHAEFER KRUSEMARK Colour System.
- FORM OF DELIVERY:** In 5 l and 15 l buckets.
- STORAGE:** Store in a cool but frost-free place. Storage time should not exceed 12 months. Reseal opened buckets tightly and use up as soon as possible.
- YIELD:**  
5 l = 20 - 25 m<sup>2</sup>  
15 l = 60 - 75 m<sup>2</sup>.  
Depending on the absorptivity of the underground.
- PROCESSING:** QUARZGRUND must be stirred well before processing.  
Applied undiluted using a brush or roller as a primer coat.  
When used to prevent premature drying out, QUARZGRUND can be diluted with max. 10% water directly before treatment.  
QUARZGRUND can be pigmented using a colouring pigment if required. Before the application of quality graded textured plasters, QUARZGRUND must be completely dry, i.e. a drying time of at least 24 hours is required.  
QUARZGRUND may not be applied under 5°C in temperature of the air or plaster base. This also applies until it has dried out.
- SAFETY NOTICE:** Avoid contact with the eyes and the skin.  
Details are shown in the safety data sheet.

The above information is based on tests and experience and represents a general guideline. It cannot be transferred to every specific application and does not release the user from the obligation of carrying out his own tests and trials. The generally recognised and technical rules of building technology as well as relevant standards and guidelines apply. Technical information about further products and our technical consultancy service are available on request. We reserve the right to make technical changes in the interests of ongoing development. In addition, our General Terms and Conditions of Business apply. Revision date: February 2015.

SCHAEFER KRUSEMARK GmbH & Co. KG

Louise-Seher-Str. 6

D-65582 Diez/Germany

Tel. +49 (0) 64 32 / 503 - 0

Fax: +49 (0) 64 32 / 503 - 119

E-Mail: [info@schaefer-krusemark.de](mailto:info@schaefer-krusemark.de)

Internet: [www.schaefer-krusemark.de](http://www.schaefer-krusemark.de)